CERTIFICATE OF COMPLIANCE

E514085 Certificate Number

E514085-20200603 Report Reference 2022-NOVEMBER-04 **Issue Date**

> RED SKY LIGHTING, LLC Issued to:

> > 410 Main Street.

RACINE, WI 53403 United States

This certificate confirms that representative samples of EMERGENCY LIGHTING AND POWER EQUIPMENT FOR

USE IN HAZARDOUS LOCATIONS

See Addendum page for Models

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

UL 844 - Luminaires for Use in Hazardous (Classified) Standard(s) for Safety:

Locations:

UL 924 - Emergency Lighting and Power Equipment.

Additional Information: See UL Product iQ® at https://ig.ulprospector.com for

additional information.


This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Assessment Director





CERTIFICATE OF COMPLIANCE

E514085 **Certificate Number**

E514085-20200603 **Report Reference** 2022-NOVEMBER-04 **Issue Date**

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Products	Product Designation
Covered Class I, Division 2, Groups A, B, C and D; Class II, Division 1, Groups E, F and	LNR
G	Followed by -40, -80, followed by -120-277, followed by -3000K, -4000K, -5000K or -5700K, followed by 110, followed by H2, followed by -CLR or -DIFF, followed by -PEND or - YOKE, STAN, CHAIN, RING, followed by -GRY, -BLK, -WTE or -BRZ, followed by -EM.
Class I, Division 2, Groups A, B, C and D; Class II, Division 1, Groups E, F and G	LNR; Followed by -40, or -80; Followed by - 120-277; Followed by -3K, -4K, -5K; Followed by -H2; Followed by -CP or -DP; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by - PND or -YKE; Followed by -EM.
	1 – Fixture Series LNR - For all luminaries 2 – Wattage 40 - 40W 80 - 80W 3 – Voltage 120-277 - 120-277V AC
	4 – Color Temperature 3K - 3000K 4K - 4000K 5K - 5000K 57K - 5700K
	5 – Hazloc Rating H2 - C1D2 / C2D1 / C3 6 – Lens CP - Clear PC
)(n ^r)(n ^r)(n ^r)(n ^r)	DP - Diffuse PC 7 - Finish Color GRY - Grey
$(U_L)(U_L)(U_L)(U_L)$	BLK - Black WHT - White BRZ - Bronze
	8 – Mounting



Conformity Assessment Director



CERTIFICATE OF COMPLIANCE

Certificate Number

E514085

Report Reference Issue Date E514085-20200603 2022-NOVEMBER-04

)(nf)(nf)(nf)(nf	PND - Pendant YKE - Yoke 9 – Battery EM – 90 mins
M UI M UI M UI M UI	

Bambles

Bruce Mahrenholz, Conformity Assessment Director

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pl contact UL Customer Service at http://ul.com/aboutul/locations/

