Certificate of Compliance

Certificate Number:

[E494317]

Report Reference:

E494317-20170717

Issue Date:

2023-DECEMBER-19

Issued to:

Red Sky Lighting, LLC

410 Main Street Racine WI 53403 US

This certificate confirms that representative samples of: LUMINAIRES, NONRECESSED, MARINE See addendum page for models

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

UL 1598 - Luminaires

UL 1598A - Supplemental Requirements for Luminaires for Installation on Marine Vessels

Additional Information:

See UL Product iQ[®] at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch

UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

Certificate of Compliance

Certificate Number: E494317

Report Reference: E494317-20170717 **Issue Date**: 2023-DECEMBER-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LNR2. Followed by -30, -40, -60 or -80. Followed by -100-277, -347-480. Followed by -27K, -3K, -4K, -5K, -65K, -RD, -GN, -BU or -AM. Followed by -H2 or -HS. Followed by -CP or -DP.

Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

1 -Series Type

LNR2 - For all luminaires.

2 – Wattage

30 - 30 W, 40 - 40 W, 60 - 60 W, 80 - 80 W.

3 -Voltage

100-277- 100~277Vac,

347-480 - 347~480Vac.

4 - Designates LED Color temperature (CCT).

27K - 2700K,3K - 3000K,4K - 4000K,5K - 5000K,57K - 5700K,

65K-6500K,RD-Red,GN-Green,

BU - Blue, AM - Amber.

5 – Basic Model Series.

H2- For all luminaires.

HS -For UL1598/A

6 - Lens Type.

CP- Clear PC.

DP- Diffused PC.

7 –Color of Finish.

GRY - Grey,

BLK - Black,

WHT - White,

BRZ - Bronze.

8 -Mounting.

PND - Pendant

YKE - Yoke.

