

Issued to:

RED SKY LIGHTING, LLC 410 MAIN STREET RACINE, WI 53403 USA

This certificate confirms that representative samples of:

LIGHT-EMITTING-DIODE SURFACE-MOUNTED LUMINAIRES

See Addendum Page

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

[UL 1598 & CSA C22.2 No. 250.0-08 - Luminaires

**UL 8750 - Light Emitting Diode (LED) Equipment for Use in Lighting Products** 

CSA-C22.2 No. 250.13 & CSA C22.2 No. 250.13-17- Light Emitting Diode (LED) Equipment for Lighting Applications]

Additional Information:

See UL Product iQ<sup>®</sup> at <a href="https://iq.ulprospector.com">https://iq.ulprospector.com</a> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

**David Piecuch** 

**UL Mark Certification Program Owner** 

**UL** Solutions

**Certificate Number:** 

[E494316]

Report Reference:

E494316-20170717

**Issue Date:** 

2024-JANUARY-09

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <a href="https://www.ul.com/contact-us">https://www.ul.com/contact-us</a>.

## **Certificate of Compliance**

Certificate Number: E494316

**Report Reference:** E494316-20170717 **Issue Date:** 2024-JANUARY-09

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## Luminaires:

LNR2-30-100-277 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

LNR2-40-100-277 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

LNR2-40-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

LNR2-60-100-277 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

LNR2-60-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

LNR2-80-100-277 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

LNR2-80-347-480 followed by -27K, -3K, -4K, -5K, -57K, -65K, -RD, -GN, -BU or -AM. followed by -H2 or -HS. followed by -CP or -DP. followed by -GRY, -BLK, -WHT or -BRZ. followed by -PND or -YKE.

