

CERTIFICATE OF COMPLIANCE

Certificate Number E514086
Report Reference E514086-20200603
Issue Date 2022-October-13

Issued to: Red Sky Lighting, LLC
410 Main Street
Racine, WI 53403 United States

This certificate confirms that representative samples of Emergency Lighting and Power Equipment
See Addendum Page


Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 924 Emergency Lighting and Power Equipment
Additional Information: See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E514086
Report Reference E514086-20200603
Issue Date 2022-October-13


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

LNT-80-120-277-**-@-# (b)

(b) - Where “**” may be CG or DG; Where “@” may be 60, T2 or 110°; Where “#” may be optional D or W.

LNT; Followed by -80; Followed by -120-277; Followed by -3K, -4K, -5K; Followed by -110, -60 or -T2; Followed by -H1; Followed by -CG or -DG; Followed by -GRY,-BLK, -WHT or -BRZ; Followed by -PND or -YKE; Followed by -EM.

1 – Fixture Series
LNT - For all luminaires
2 – Wattage
80 - 80W
3 – Voltage
120-277 - 120-277V AC
5 – Beam Angle
110 - 110°
60 - 60°
T2 - Type II
6 – Luminaire Series
H1 - For all luminaires
7 – Lens
CG - Clear Glass
DG - Diffuse Glass
8 – Finish Color
GRY - Grey
BLK - Black
WHT - White
BRZ - Bronze
9 – Mounting
PND - Pendant
YKE - Yoke
10 – Battery
EM – 90 mins



Bruce Mahrenholz, Conformity Assessment Director
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Customer Service at <http://ul.com/aboutul/locations/>

