

# Certificate of Compliance

**Certificate Number:**

[E494317]

**Report Reference:**

E494317-20231219

**Issue Date:**

2023-DECEMBER-19

Issued to:

**Red Sky Lighting, LLC**

410 Main Street Racine WI 53403 US |

This certificate confirms that representative samples of:  
**LUMINAIRES, NONRECESSED, MARINE**  
**See addendum page for models**

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

**[UL 1598 - Luminaires  
UL 1598A - Supplemental Requirements for Luminaires for  
Installation on Marine Vessels]**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# Certificate of Compliance

**Certificate Number:** E494317  
**Report Reference:** E494317-20170717  
**Issue Date:** 2023-DECEMBER-19

LNT2. Followed by -30, -40, -60 or -80. Followed by -120-277, 347-480. Followed by -27K, -3K, -4K, -5K, -57K,-65K. Followed by -110, -60 or -T2. Followed by -H1 or HS. Followed by -CG or -DG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE. Followed by BLANK or -PS.

1 –Series Type

LNT2 – For all luminaires.

2 – Wattage 30 – 30 W,40 – 40 W,60 – 60 W,80 – 80 W.

3 –Voltage

120-277- 120~277Vac,347-480 - 347~480Vac.

4 – Designates LED Color temperature (CCT).

27K – 2700K,3K – 3000K,4K – 4000K,5K – 5000K,57K – 5700K,65K– 6500K.

5 –Optic Beam Angle.

60 - 60°,T2 - Type II ,110 – 110° (non-optic).

6 –Basic Model Series.

H1 –For all luminaires,HS- 1598/A.

7 - Lens Type.

CG- Clear Glass.DG- Diffused glass.

8 –Color of Finish.

GRY - Grey,BLK - Black,WHT - White,BRZ - Bronze.

9 –Mounting.

PND - Pendant

YKE - Yoke.

10 - Paint Spray.

Blank – Non Paint Spray Use

PS – Paint Spray Use.