Certificate of Compliance

Certificate Number:

E494317

Report Reference:

E494317-20240416

Issue Date:

2024-APRIL-16

Issued to:

Red Sky Lighting LLC 9370 Pittsburgh Ave Rancho Cucamonga, CA, US, 91730-5557

This certificate confirms that representative samples of: LUMINAIRES, NONRECESSED, MARINE See Addendum Page for Models

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

UL 1598 Luminaires
UL 1598A Supplemental Requirements for Luminaires for Installation on Marine Vessels

Additional Information:

See UL Product iQ[®] at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch

UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

Certificate of Compliance

Certificate Number: E494317

Report Reference: E494317-20240416 Issue Date: 2024-APRIL-16

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Models: MDX [b]

[b] followed by -15L, -20L, -30L, -40L, -50L, -60L or -70L; followed by -100-277 or -347-480; followed by -65K, -57K, -5K, -4K, -3K or -27K; followed by Blank,-HAR or -XXX; followed by -30, -40, -60, -90, -120, -T1, -T2, -T3, -T4 or -T5; followed by -H2 or -HS; followed by -CG or -CP; followed by -GRY, -BLK, -WHT or -BRZ; followed by -PND, -SYK or -AYK.

