

Certificate of Compliance

Certificate Number:

[E494317]

Report Reference:

E494317-20170717

Issue Date:

2023-DECEMBER-19

Issued to:

Red Sky Lighting, LLC

410 Main Street Racine WI 53403 US |

This certificate confirms that representative samples of:
LUMINAIRES, NONRECESSED, MARINE
See addendum page for models

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

**[UL 1598 - Luminaires
UL 1598A - Supplemental Requirements for Luminaires for
Installation on Marine Vessels]**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



Certificate of Compliance

Certificate Number: E494317
Report Reference: E494317-20170717
Issue Date: 2023-DECEMBER-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

RND2. Followed by -35, -40, -45, -55, -60 or -65. Followed by -120-277, -347-480. Followed by -27K, -3K, -4K, -5K, -57K, -65K. Followed by -60 or -120. Followed by H2 or HS. Followed by -CG, DG or -DLG. Followed by -GRY, -BLK, -WHT or -BRZ. Followed by -PND or -YKE.

1 –Series Type

RND2 – For all luminaires.

2 – Wattage

35 – 35 W (120~277 Vac),

40 – 40 W (347~480Vac),

45 – 45 W (120~277 Vac),

55 – 55 W (120~277 Vac),

60 – 60 W (347~480Vac),

65 – 65 W (120~277 Vac),

3 –Voltage

120-277- 120~277Vac,

347-480 - 347~480Vac.

4 –LED Color temperature (CCT).

27K – 2700K,3K – 3000K,4K – 4000K,5K – 5000K,57K – 5700K,65K– 6500K.

5- Optic Beam Angle.

60 - 60°,

120 - 120°(non-optic).

6 –Basic Model Series.

H2 – For all luminaires

HS-UL1598/A

7 - Lens Type.

CG- Clear Glass.DG- Diffuse Glass,

DLG- Diffuse Drop Lens Glass.

8 –Color of Finish.

GRY - Grey,BLK - Black,WHT - White,BRZ - Bronze.

9 –Mounting.

PND - Pendant

YKE – Yoke